

AMENDMENT TO THE CLAIMS

1. (Canceled)

2. (Currently amended) ~~A wireless LAN apparatus as claimed in claim 1~~ A wireless LAN apparatus comprising:

as a transmitting-side configuration thereof,

a packet length controlling unit,

the packet length controlling unit controlling a packet length of transmit data;

a packet synthesizing unit,

the packet synthesizing unit synthesizing the number of the transmit data corresponding to the packet length controlled by the packet length controlling unit into a packet transmit data and outputting the transmit packet data;

a frame synthesizing unit,

the frame synthesizing unit appending the packet-length information to a header information of the transmit packet data synthesized by the packet synthesizing unit and outputting the transmit packet data as a transmit frame; and

a wireless transmit unit,

the wireless transmit unit transmitting wirelessly the transmit frame output by the frame synthesizing unit, wherein

the packet length controlling unit comprises a packet length register, the packet length register capable of externally controlling the packet-length information.

3. (Original) A wireless LAN apparatus as claimed in claim 2, wherein
the packet length controlling unit comprises:

a timer, the timer restarting based on an input of a reset signal;
a timer termination register,
the time termination register instructing a count termination value of the timer; and
a force-transmit instructing device,
the force-transmit instructing device outputting a transmit instructing signal to the packet synthesizing unit when a count value counted by the timer agrees with the count termination value instructed by the timer termination register, and wherein

the packet synthesizing unit outputs the reset signal to the timer based on the output of the transmit packet data and prioritizes the transmit packet data over the packet-length information from the packet length register when the transmit instructing signal from the force-transmit instructing unit is input thereto to thereby output immediately the transmit packet data.

4. (Original) A wireless LAN apparatus as claimed in claim 2 further comprises,
as the transmitting-side configuration thereof,

a data rate detecting unit,
the data rate detecting unit detecting a transmit rate of the transmit data input to the packet synthesizing unit and outputting the detection result as a data rate detection signal,
wherein

the packet length controlling unit further comprises
a packet-length rate controlling device,
the packet-length rate controlling device increasing or decreasing the packet-length information from the packet length register based on the data rate detection signal from the data

rate detecting unit.

5. (Currently amended) ~~A wireless LAN apparatus as claimed in claim 1 further~~

~~comprises:~~ A wireless LAN apparatus comprising:

as a transmitting-side configuration thereof,

a packet length controlling unit,

the packet length controlling unit controlling a packet length of transmit data;

a packet synthesizing unit,

the packet synthesizing unit synthesizing the number of the transmit data corresponding to the packet length controlled by the packet length controlling unit into a packet transmit data and outputting the transmit packet data;

a frame synthesizing unit,

the frame synthesizing unit appending the packet-length information to a header information of the transmit packet data synthesized by the packet synthesizing unit and outputting the transmit packet data as a transmit frame; and

a wireless transmit unit,

the wireless transmit unit transmitting wirelessly the transmit frame output by the frame synthesizing unit,

wherein the wireless LAN apparatus further comprises:

as a receiving-side configuration thereof,

a wireless receive unit,

the wireless receive unit receiving the transmit frame transmitted wirelessly by another wireless LAN apparatus configured likewise; and

an error detecting unit,
the error detecting unit judging whether or not the received transmit frame is normally received, wherein
as the receiving-side configuration of the apparatus,
the wireless transmit unit wirelessly transmits a receive data indicating the judgment result with respect to the wireless receive unit to the another wireless LAN apparatus, and
the wireless LAN apparatus further comprises,
as the transmitting-side configuration thereof,
a retransmit controlling unit,
the retransmit controlling unit requesting the wireless transmit unit to retransmit the same transmit frame when it is judged that an transmission error occurred from the receive data, wherein
as the transmitting-side configuration of the apparatus,
the packet length controlling unit further comprises:
a retransmit counting device,
the retransmit counting device counting the number of the requests for retransmission from the retransmit controlling unit;
a retransmit-count upper limit register,
the retransmit-count upper limit register setting a count upper-limit value of the retransmit counting device; and
a retransmit-packet length controlling device maintaining a value of the packet-length information when the number of the retransmission requests counted by the retransmit counting

device is smaller than the count upper-limit value set by the retransmit-count upper limit register and

decreasing the value of the packet-length information and when the number of the retransmission requests counted by the retransmit counting device agrees with the count upper-limit value set by the retransmit-count upper limit register.

6. (Currently amended) ~~A wireless LAN apparatus as claimed in claim 1 further comprises:~~ A wireless LAN apparatus comprising:
as a transmitting-side configuration thereof,
a packet length controlling unit,
the packet length controlling unit controlling a packet length of transmit data;
a packet synthesizing unit,
the packet synthesizing unit synthesizing the number of the transmit data corresponding to the packet length controlled by the packet length controlling unit into a packet transmit data and outputting the transmit packet data;
a frame synthesizing unit,
the frame synthesizing unit appending the packet-length information to a header information of the transmit packet data synthesized by the packet synthesizing unit and outputting the transmit packet data as a transmit frame; and
a wireless transmit unit,
the wireless transmit unit transmitting wirelessly the transmit frame output by the frame synthesizing unit,
wherein the wireless LAN apparatus further comprises:

as a receiving-side configuration thereof,
a wireless receive unit,
the wireless receive unit receiving the transmit frame transmitted wirelessly by another wireless LAN apparatus configured likewise; and
an error detecting unit,
the error detecting unit judging whether or not the received transmit frame is normally received, wherein
as the receiving-side configuration of the apparatus, the wireless transmit unit wirelessly transmits a receive data indicating the judgment result with respect to the wireless receive unit to the another transmitting-side wireless LAN apparatus, and
the wireless LAN apparatus further comprises,
as the transmitting-side configuration thereof,
a retransmit controlling unit,
the retransmit controlling unit requesting the wireless transmit unit to retransmit the same transmit frame as a most-recently-transmitted transmit frame when it is judged that an transmission error occurred based on the receive data and judging whether or not the retransmission is successful, wherein
as the transmitting-side configuration of the apparatus,
the packet length controlling unit further comprises:
a retransmit counting device,
the retransmit counting device counting the number of the retransmission requests from the retransmit controlling unit;
a retransmit count averaging device,

the retransmit count averaging device calculating an average value of the number of the retransmission requests when it is judged that the retransmission is successful;

a retransmit-count upper limit register,

the retransmit-count upper limit register setting a count upper-limit value of the retransmit counting device; and

a retransmit-packet length controlling device maintaining a value of a packet-length according to the most-recently-transmitted transmit frame as the packet length of the transmit data to be retransmitted when the average value calculated by the retransmit count averaging device is smaller than the count upper-limit value set by the retransmit-count upper limit register and

setting a decreased value of the packet length of the most-recently-transmitted transmit frame as the packet length of the transmit data to be retransmitted when the average value calculated by the retransmit count averaging device agrees with the count upper-limit value set by the retransmit-count upper limit register.

7. (Currently amended) A wireless LAN apparatus as claimed in claim [[1]] 2, wherein

as a receiving-side configuration of the apparatus,

the wireless transmit unit creates a packet length control frame enabling the packet length of the transmit frame transmitted by another wireless LAN apparatus to be designated by the receiving-side wireless LAN apparatus of the present invention and wirelessly transmits the packet length control frame to the another wireless LAN apparatus, further comprises:

as the transmitting-side configuration thereof,

a wireless receive unit,
the wireless receive unit receiving the packet length control frame transmitted wirelessly
by another wireless LAN apparatus configured likewise; and
a packet length control frame detecting unit,
the packet length control frame detecting unit judging the packet length control frame
received by the wireless receive unit and
outputting a packet length request-to-reduce signal when the packet length control frame
instructs the packet length to be reduced and a packet length request-to-extend signal when the
packet length control frame instructs the packet length to be extended, wherein
as the transmitting-side configuration of the apparatus,
the packet length controlling unit reduces the packet-length information when the packet
length request-to-reduce signal is input thereto and extends the packet-length information when
the packet length request-to-extend signal is input thereto.

8-9. (Canceled)

10. (Currently amended) A wireless LAN apparatus as claimed in claim [[1]] 2
comprises:

as a receiving-side configuration thereof,
a wireless receive unit,
the wireless receive unit receiving the transmit frame transmitted wirelessly by another
wireless LAN apparatus configured likewise and detecting a transmit-channel-distortion
information in the received transmit frame;

a packet extracting unit,

the packet extracting unit separating the received transmit frame into the transmit packet data and the header information;

a packet length detecting unit,

the packet length detecting unit detecting the packet-length information included in the transmit frame in the header information separated from the transmit frame by the packet extracting unit; and

a packet dividing unit,

the packet dividing unit dividing the transmit packet data separated from the transmit frame by the packet extracting unit based on the packet-length information detected by the packet length detecting unit and outputting the divided transmit packet data, wherein

as the transmitting-side configuration of the apparatus,

the packet length controlling unit controls the packet length of the transmit data based on the transmit-channel-distortion information detected by the wireless receive unit.

11. (Original) A wireless LAN apparatus as claimed in claim 10 further comprises:

as the transmitting-side configuration thereof,

a RSSI judging unit,

the RSSI judging unit judging an electric power of the received transmit frame based on the transmit-channel-distortion information detected in the transmit frame by the wireless receive unit serving to receive the transmit frame transmitted wirelessly by another wireless LAN apparatus configured likewise; and

a packet-length information creating unit,

the packet-length information creating unit creating a packet length setting signal for the transmit frame transmitted wirelessly by the wireless LAN apparatus according to the present invention based on the judgment result by the RSSI judging unit and

outputting the packet length setting signal to the packet length controlling unit, wherein as the transmitting-side configuration of the apparatus,

the packet length controlling unit control the packet length of the transmit data based on the packet length setting signal.

12. (Original) A wireless LAN apparatus as claimed in claim 10, wherein as the receiving-side configuration thereof,

the wireless receive unit outputs peak-value information indicating the status of a peak value of a correlation signal in connection with a synchronous reference symbol of the transmit frame received from another wireless LAN apparatus configured likewise, further comprises:

as the receiving-side configuration thereof,

a synchronous detection signal judging unit,

the synchronous detection signal judging unit judging the status of transmission channel for transmitting wirelessly the transmit frame based on the peak-value information; and

a packet-length information creating unit,

the packet-length information creating unit creating a packet-length setting information for the transmit data based on the judgment result by the synchronous detection signal judging unit and outputting the packet-length setting information to the packet length controlling unit, wherein

as the transmitting-side configuration of the apparatus,

the packet length controlling unit controls the packet length of the transmit data based on the packet-length setting information.

13. (Original) A wireless LAN apparatus as claimed in claim 10, wherein
as the receiving-side configuration thereof,
the wireless receive unit outputs an integral width of a correlation signal in connection with a synchronous reference symbol of the transmit frame received from another wireless LAN apparatus configured likewise, further comprises:

as the receiving-side configuration thereof,
a synchronous detection signal judging unit,
the synchronous detection signal judging unit judging the status of transmission channel for transmitting wirelessly the transmit frame based on the integral width; and

a packet-length information creating unit,
the packet-length information creating unit creating a packet-length setting information for the transmit data based on the judgment result by the synchronous detection signal judging unit and outputting the packet-length setting information to the packet length controlling unit,
wherein

as the transmitting-side configuration of the apparatus,
the packet length controlling unit controls the packet length of the transmit data based on the packet-length setting information.

14. (Original) A wireless LAN apparatus as claimed in claim 10, wherein
as the receiving-side configuration thereof,

the wireless receive unit outputs a constellation distortion signal based on a difference between an actual mapping value and an ideal mapping value of the transmit frame received from another wireless LAN apparatus configured likewise, further comprises:

as the receiving-side configuration thereof,

a synchronous detection signal judging unit,

the synchronous detection signal judging unit detecting the status of transmission channel for transmitting wirelessly the transmit frame based on the constellation distortion signal; and

a packet-length information creating unit,

the packet-length information creating unit creating a packet-length setting information for the transmit data based on the judgment result by the synchronous detection signal judging unit and outputting the packet-length setting information to the packet length controlling unit, wherein

as the transmitting-side configuration of the apparatus,

the packet length controlling unit controls the packet length of the transmit data based on the packet-length setting information.

15. (Original) A wireless LAN apparatus as claimed in claim 10, wherein
as the receiving-side configuration thereof,
the wireless receive unit outputs a Viterbi error count signal based on a difference between a branch metric according to a maximum-likelihood path and a branch metric according to other than the maximum-likelihood path, further comprises:

as the receiving-side configuration thereof,

a synchronous detection signal judging unit,

the synchronous detection signal judging unit judging the status of transmission channel for transmitting wirelessly the transmit frame based on the Viterbi error count signal; and

a packet-length information creating unit,

the packet-length information creating unit creating a packet-length setting information for the transmit data based on the judgment result by the synchronous detection signal judging unit and outputting the packet-length setting information to the packet length controlling unit, wherein

as the transmitting-side configuration of the apparatus,

the packet length controlling unit controls the packet length of the transmit data based on the packet-length setting information.

16. (Currently amended) A wireless LAN apparatus as claimed in claim [[1]] 2 further comprises:

as a receiving-side configuration thereof,

a wireless receive unit,

the wireless receive unit receiving the transmit frame transmitted wirelessly by another wireless LAN apparatus configured likewise;

a packet extracting unit,

the packet extracting unit separating the received transmit frame into the transmit packet data and the header information;

a packet length detecting unit,

the packet length detecting unit detecting the packet-length information included in the transmit frame in the header information separated from the transmit frame by the packet extracting unit;

a packet dividing unit,

the packet dividing unit dividing the transmit packet data separated from the transmit frame by the packet extracting unit based on the packet-length information detected by the packet length detecting unit and outputting the divided transmit packet data; and

a receive-accuracy information creating unit,

the receive-accuracy information creating unit creating a receive-accuracy information signal based on the packet length setting signal used for controlling the packet length in the packet length controlling unit, wherein

as the transmitting-side configuration of the apparatus,

the wireless receive unit controls a bit width for receive processing and an accuracy for processing a retained volume of receive data based on processing and an accuracy for processing a receive-data retained volume based on the receive-accuracy information signal.